

# SR-70

## 360° STAINLESS STEEL HARDWIRED ROAD STUD



### KEY FEATURES

- 360° View
- Highly resistant to impact and corrosion
- Robust construction, suitable for harsh conditions
- Snow plough resistant
- High brightness day or night
- Possibility of integration with control traffic devices
- Suitable for applications in roads, tunnels, parks and airports
- Communication protocol (optional)
- Hardwired system for solar powered or electrical
- Operation Mode: Always on, Flashing, Sequential

### SPECIFICATIONS:

#### ELECTRICAL

Power Supply: 12Vdc or 24Vdc  
Current Consumption: 160mA

#### OPTICAL

LEDs Number: 24 LEDs - 5mm  
LEDs Colour: Amber, Red, White, Blue, Green  
LEDs Configuration: Omni-directional - possibility of using different LED colors in each window

#### MECHANICAL

Dimensions:  $\varnothing 190\text{mm} \times 107.7\text{mm}$   
Weight: 3.5Kg  
Projection: 15.2mm  
Minimum Installation Depth: 100mm  
Bottom Part Material: Aluminium  
Top Material: Stainless Steel League  
Mechanical Resistance: 160 Tons  
Protection Index: IP68 and IK10


### OTHER VERSIONS

#### SR-70 P

- Ultra brightness road stud with high power LEDs
- Up to 8 power LEDs (1W) with internal lens, providing a high light intensity
- Specially developed heat sink to increase LEDs lifetime

#### SR-70 RGB

- Road Stud with high brightness RGB LEDs
- Multiple colors in one piece



Dimensions: mm



ROAD MARKING - SIGNING - TRAFFIC LIGHTING  
TRAFFIC SAFETY PRODUCTS AND SOLUTIONS  
Tel: 0030 2105233128 Fax: 0030 2105231770  
Web: www.diasimco.gr Email: info@diasimco.gr