I-STUD EVOLUTION SR-i15E

i-stud evolution technology applied to **SR-i15E** increase the performance of solar power studs with energy storage by battery or capacitor. The main advantage of i-stud evolution is the use of microcontroller technology inside each stud, which allows several beneficial features and control options.

KEY FEATURES

Wake Up/Sleep Function

Allows the stud to stay in "sleep" mode before the application, extending the autonomy of the battery

Automatic Brightness Control

Manages the energy stored, adapt the brightness and regulate its light level in accordance with the energy charged during the

Definition of the Working Period

Set up the number of hours the i-stud should work after night detection, when roads studs do not have to operate all night

Operation Mode Flash/Always ON

Switch the stud's mode from 'flashing' to 'always on' and vice versa after installation

Adaptation of the flash rate after installation

Night Level Detection

Adjustment of the lighting level detection (Lux)

Operation Mode Uni or Bi-directional

Modify the light direction temporarily or permanently

Low Temperature

Detects the possibility of ice forming on roads and change the LEDs colour to warn drivers about the dangerous weather condition

If a problem with the stud is detected the unit is able to make an internal log to discover what are the causes of the problem

SPECIFICATIONS:

LEDs Number: 1 or 2 LEDs (uni-directional), 2 or 4 LEDs (bi-di-

rectional) - 5mm LEDs Colour: Amber, Red, White, Blue, Green

MECHANICAL Dimensions: Ø144.6mm x 50mm

Weight: 0.5Kg Projection: 12.7mm

Minimum Installation Depth: 50mm Material: Aluminium, Polycarbonate Mechanical Resistance: 60 Tons Protection Index: IP68 and IK10

STANDARD VERSION

Non programmable stud with basic functions



ROAD MARKING - SIGNING - TRAFFIC LIGHTING TRAFFIC SAFETY PRODUCTS AND SOLUTIONS Tel: 0030 2105233128 Fax: 0030 2105231770

Dimensions: mm







